



ARP 643443N 0165023E

AD ELEV 1141 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge CL HLDG	Centerline EDGE	RGL Stopbar
A	15 m	ASPH PCN 12 F/B/X/U	CL HLDG		EDGE	RGL
TO HANGAR	10 m	ASPH	CL			

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
ASPH PCN 12 F/B/X/U			

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation END PSN	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
10	103.14° GEO 096° MAG	643450.20N 0164905.97E GUND 96 ft END RWY: 643439.18N 0165055.73E	PCN 12 F/B/X/U	THR 1139 ft	1500	1500	1500	1500	SALS 420 m LIL/LIH	THR Green	PAPI Left/3.00° (21.7 ft)	1500/60 m White Caution zone 600 m yellow LIL/LIH	Red
28	283.17° GEO 276° MAG	643440.96N 0165038.13E GUND 96.4 ft	PCN 12 F/B/X/U	THR 1139.2 ft TDZ 1140 ft	1500	1500	1500	1260	Calvert Cat I 900 m LIL/LIH	THR Green	PAPI Left/3.00° (49.2 ft)	1500/60 m White Caution zone 600 m yellow LIL/LIH	Red

REMARK :
THR 28 permanently displaced 241 m. Supplementary approach lighting is inset into the runway.

