

ARP 592116N 0175632E

LEGEND See GEN 2.3

AD ELEV 47 FEET

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL STOPBAR
G1	20 m	PCN 15 F/B/X/T	CL HLDG	EDGE	RGL STOPBAR	RGL STOPBAR
R	16 m	PCN 46 F/A/X/T	CL	CL		
S	15 m	PCN 30 F/A/X/T	CL	CL		
T	19 m	PCN 66 F/C/X/T	CL	CL		
Y	19 m	PCN 51 F/A/X/T	CL	CL		
Y1	19 m	PCN 59 F/A/X/T	CL HLDG	CL	RGL STOPBAR	
Y2	20 m	PCN 59 F/A/X/T	CL ITHP	CL		
Y3	19 m	PCN 81 F/A/X/T	CL HLDG	CL	RGL STOPBAR	
Y4	19 m	PCN 51 F/A/X/T	CL HLDG	CL	RGL STOPBAR	
Y5	19 m	PCN 51 F/A/X/T	CL HLDG	CL	RGL STOPBAR	
YU	24 m	PCN 95 F/A/X/T	CL ITHP	CL		
YW	24 m	PCN 95 F/A/X/T	CL ITHP	CL		

REMARK: Pilot will receive instructions to change to GND frequency from TWR after landing.

INS Coordinates for Aircraft Stands			
APRON Bearing strength	NR	COORD	ELEV
Apron 1 ASPH PCN 82 F/B/X/T	3	592118.27 N 0175641.31 E	18
	4	592119.31 N 0175638.60 E	17
	5	592120.29 N 0175635.90 E	18
	6	592121.09 N 0175633.30 E	18
Apron 2 ASPH PCN 71 F/B/X/T	7	592123.37 N 0175630.63 E	18
	8	592122.78 N 0175632.72 E	18
	9	592121.82 N 0175635.41 E	17
	10	592120.96 N 0175639.17 E	18
	11	592123.33 N 0175640.65 E	16
	12	592125.10 N 0175639.26 E	15
	13	592126.18 N 0175636.24 E	16
Apron 3 ASPH PCN 76 F/B/X/T	14	592127.26 N 0175633.22 E	18
	15	592128.16 N 0175630.31 E	18
	16	592128.95 N 0175633.26 E	19
	17	592128.02 N 0175635.87 E	18
Apron East ASPH PCN 95 F/A/X/T (W part: PCN 23 F/A/X/T)	18	592126.93 N 0175638.93 E	16
	19	592125.84 N 0175641.98 E	15
Apron 4 ASPH PCN 44 F/B/X/T			
Apron 6 ASPH PCN 15 F/A/X/T			
Apron 7 ASPH PCN 19 F/B/X/T Narrow part connecting to TWY S PCN 29 F/B/X/T			
Apron Remote North ASPH PCN 60 F/A/X/T			

