



TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	
2	18 m	ASPH PCN 60 F/C/X/T	CL	EDGE		
4	18 m	ASPH PCN 20 F/C/Y/T	CL	EDGE		
5	15 m	ASPH PCN 20 F/C/X/T	CL	EDGE		
A	24 m	ASPH PCN 60 F/B/X/T	CL HLDG	EDGE	RGL	
B	23 m	ASPH PCN 40 F/B/X/T	CL HLDG	EDGE	RGL	
C	44 m	ASPH PCN 40 F/B/X/T	CL HLDG	EDGE	RGL	
E	15 m	ASPH PCN 40 F/B/Y/U	CL HLDG			
F	10 m	ASPH PCN 20 F/B/Y/U	CL HLDG	EDGE		
G	8 m	ASPH PCN 20 F/B/Y/U	CL HLDG	EDGE		

**ARP** 584719N 0165413E  
**AD ELEV** 142 FEET

**LEGEND** See GEN 2.3  
 Dimensions in m, ELEV in ft

**REMARK:**  
 Apron 4:  
 Max wing span 36 m. Parking coordination required (Skavsta Operations, freq. 130.180).  
 Marshalling available O/R (TWR).

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
1 ASPH PCN 40 F/B/X/T			
2 ASPH PCN 60 F/B/X/T			
4 ASPH PCN 20 F/C/Y/T			
5 ASPH PCN 20 F/C/X/T			

Reverse side intentionally blank